



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7929 N Sam Houston Pkwy W Suite 100  
77064-0000, TX Houston  
Phone: 281-345-1143  
Fax: 281-345-7697



## **E10168362 E1016 M P NV DSS 2/0 to 4** *Crouse-Hinds*

Catalog Number	E10168362
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Cam-Lok J Series E1016 Plug, Up to 400A Continuous, 2/0-4/0 Awg, Black, Double Set Screw, Brass Contacts, Male, Thermoplastic Elastomer (Tpe), Non-Vulcanized, 600 Vac/DC
Weight per unit	0.6000 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out

### **Features**

amperage rating	400
connection	Double Set Screw
dimensions	7.1800 IN X 1.5000 IN X 1.5000 IN
Poles	1
Voltage Rating	600 VAC/VDC
Wire Size	2/0 To 4/0 AWG

### **Dimensions and Weight**

Size	1.50 In Diameter X 7.18 In Length
------	-----------------------------------

### **Descriptions**

Description	E1016 M P NV DSS 2/0 TO 4
extra long description	CRS-H E1016-8362 E1016 M P NV DSS 2
Features	The Cam-Lok J series from Eaton's Crouse-Hinds Division provides the means to quickly connect and disconnect power systems safely. Cam-Lok is the industry standard for motors, generators, indoor and outdoor lighting distribution panels, and numerous other power applications.
Long Description	Eaton Crouse-Hinds series Cam-Lok J Series E1016 plug, Up to 400A continuous, 2/0-4/0 AWG, Black, Double set screw, Brass contacts, Male, Thermoplastic elastomer (TPE), Non-vulcanized, 600 Vac/dc
Product Type	E1016 M P NV DSS 2/0 to 4/0 BK
Special Features	NEMA 3R Enclosure

### **Manufacturer Information**

Brand	Eaton
GTIN	00662275131638
Manufacturers Part Number	E1016-8362
UPC	662275131638



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7929 N Sam Houston Pkwy W Suite 100  
77064-0000, TX Houston  
Phone: 281-345-1143  
Fax: 281-345-7697

## Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	PLUG

## Packaging

Carton	1
Package	10
Weight Per each	0.6

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
environmental conditions	-40 To 105 Deg C
standard	UL, CSA