



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

926 Hwy 19
77320-0000, TX Huntsville
Phone: 936-439-0658
Fax: 936-439-9182



EDS3129 FS Gen Use Snap SWITCH

Crouse-Hinds

Catalog Number	EDS3129
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eds Snap Switch Control Station, 20A, With Switch, With One 1" Hub, Feraloy Iron Alloy, 1, Single-Gang, Single-Pole, 120-277V, Factory Sealed, Dead End, Single-Pole, 1", 120-277 Vac
Weight per unit	7.9 (lbs/each)
Product Category	Selector Switch Complete Assem

Features

action	SP
amperage rating	20A
dimensions	5.0600 IN X 3.5000 IN X 5.8750 IN
Material	FERALOY IRON ALLOY
Poles	Single-pole
Voltage Rating	120-277 VAC

Dimensions and Weight

Size	5-7/8 In Length X 3-1/2 In Width X 3-1/16 In Height
------	---

Descriptions

Description	FS GEN USE SNAP SWITCH
extra long description	CRS-H EDS3129 EDS FS GENERAL USE SN
Features	New EDSX series available with NEMA 4X protection for Class I, Division 2 hazardous areas.EDS/EDSX and EFD snap switches are used with magnetic starters or contactors for control of motors. Snap switch control stations are factory sealed to prevent arcing of the enclosed device from causing ignition of a hazardous atmosphere external to the enclosure. Factory sealing eliminates the need for external seals, simplifying installation and reducing material and labor costs.
Long Description	Eaton Crouse-Hinds series EDS snap switch control station, 20A, With switch, With one 1" hub, Feraloy iron alloy, 1, Single-gang, Single-pole, 120-277V, Factory sealed, Dead end, Single-pole, 1", 120-277 Vac
Product Type	Eds FS General Use Snap Switch
Special Features	Factory sealed



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

926 Hwy 19
77320-0000, TX Huntsville
Phone: 936-439-0658
Fax: 936-439-9182

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274764009
Manufacturers Part Number	EDS3129
UPC	782274764009

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION MOTOR CONTROL
Type	Snap switch control station

Packaging

Carton	1
Weight Per each	7.89

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 Group E F G, Class II Div 2
standard	Group F G, Class III, NEMA 3/7B/7C/7D/9E/9F/9G UL 1203, CSA C22.2