

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EDSC218 3/4" 1G 2P Sel Switch Encl *Crouse-Hinds*

EDSC218
Crouse-Hinds
Eaton Crouse-Hinds Series Eds Snap Switch Control Station, 20A, With Switch, With Two 3/4" Hubs, Feraloy Iron Alloy, 1, Single-Gang, Two-Pole, 120-277V, Factory Sealed, Through Feed, Two-Pole, 3/4", 120-277 Vac
8.5 (lbs/each)
Selector Switch Complete Assem
20A
5.0600 IN X 3.5000 IN X 5.8750 IN
FERALOY IRON ALLOY
Two-pole
120-277 VAC

Dimensions and Weight

Size	5-7/8 In Length	ı X 3-1/2 In Width X 2-	-11/16 In Height

Descriptions

Description	3/4" 1G 2P SEL SWITCH ENCL
extra long description	CRS-H EDSC218 EDS FS GENERAL USE SN
Features	New EDSX series available with NEMA 4X protection for Class I, Division 2 hazardous areas. EDS/EDSX and EFD snap switches are used with magnetic starters or contactors for control of motors. Snap switch control stations are factory sealed to prevent arcing of the enclosed device from causing ignition of a hazardous atmosphere external to the enclosure. Factory sealing eliminates the need for external seals, simplifying installation and reducing material and labor costs.
Long Description	Eaton Crouse-Hinds series EDS snap switch control station, 20A, With switch, With two 3/4" hubs, Feraloy iron alloy, 1, Single-gang, Two-pole, 120-277V, Factory sealed, Through feed, Two-pole, 3/4", 120-277 Vac
Product Type	Eds FS General Use Snap Switches
Special Features	Factory sealed
nufacturer Information	

Manufacturer Information

Brand	Eaton
GTIN	00782274765280
Manufacturers Part Number	EDSC218
UPC	782274765280



Enclosure

standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	STANDARD DUTY PUSHBUTTONS (10250H-)
Туре	Snap switch control station
Packaging	
Carton	1
Weight Per each	8.5
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Power Distribution and Control

UL 1203, CSA C22.2

NEMA 3/7B/7C/7D/9E/9F/9G