



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln
79109-3210, TX Amarillo
Phone: 806-220-0404
Fax: 806-220-0811



ELM2LM12 Led Emergency 220LM 120-347V Bugeye White

Lithonia Lighting - Acuity

Catalog Number	ELM2LM12
Manufacturer	Lithonia Lighting - Acuity
Description	The Quantum® Series From Lithonia Lighting® With Improved Aesthetics and Performance, Is Easy to Install and Maintain. The Advanced Optical Design and Electronic Technology Deliver High-Quality Light Output When It Is Needed Most.
Weight per unit	1.8 (lbs/each)
Product Category	Emergency Lighting

Features

dimensions	9.72 x 4.68 x 4.68
Fixture Type	Emergency Lighting Unit
Hardware	No
Lamp Included	Yes
Lamp Type	LED - Static
lumens	220
Material	Thermoplastic
Power Source	Hardwired
Voltage Rating	120/277 V
Warranty	5
Wattage	0.36

Material, Color, and Finish

Color	White
color rendering index (cri)	70
color temperature	5000
Finish	Textured
Lens Color	Clear
Lens Material	Acrylic

Dimensions and Weight

Height	4.68
Length	9.72
Width	3.1



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln
79109-3210, TX Amarillo
Phone: 806-220-0404
Fax: 806-220-0811

Descriptions

Construction	New Construction,Remodel
Description	LED EMERGENCY 220LM 120-347V BUGEYE WHITE
extra long description	LITH ELM2L M12 ELM2L
Features	Contractor Select
Long Description	The Quantum® series from Lithonia Lighting® with improved aesthetics and performance, is easy to install and maintain. The advanced optical design and electronic technology deliver high-quality light output when it is needed most.
Product Type	Emergency Lighting Unit

Manufacturer Information

Brand	Lithonia Lighting
GTIN	00191848091920
Manufacturers Part Number	ELM2L M12
UPC	191848091920

Taxonomies, Classifications, and Categories

Category Description	Emergency & Exit Lighting
Type	Emergency Lighting Unit

Packaging

Carton	1
Package	12
Weight Per each	1.7999

Uses, Certifications, and Standards

Application	Education,Government,Healthcare,Hospitality,House of Worship,Offices & Banks,Residential,Retail,Sports and Recreation
environmental conditions	Indoor,Outdoor
Mounting	SURFACE
standard	C-UL-US,NFPA 101,NFPA 70,NOM,ULCA Title 20