SSP INTUMESCENT PUTTY PADS



Externally applied to switch and receptacle boxes, pads are UL Tested and Classified to permit larger boxes and reduced spacing in gypsum board walls.

FEATURES & BENEFITS:

- Fits common 4S box with no cutting or trimming.
- Two-Stage intumescence provides aggressive expansion.
- Highly adhesive: stays put.
- Unaffected by humidity, condensation, water.
- Soft, pliable, easy to install.
- Tested and proven acoustical properties.
- Poly liner allows hands-off, clean installation.



APPLICATIONS

- Single & multi-gang metallic boxes up to 14" (356 mm) long.
- A variety of non-metallic boxes.
- Plastic & steel faceplates.
- 1& 2 hr. wood or steel stud walls.






ORDERING INFORMATION					
UPC #	Part #	Description	Qty.	Case Qty.	Weight Each - lbs.
02200	SSP4S	Putty Pad 7.25" x 7.25" x 3/16"	1	20	0.59
02300	SSP9S	Putty Pad 9.00" x 9.00" x 3/16"	1	20	0.99



ELECTRICAL BOX INSERTS

POWERSHIELD™ ELECTRICAL BOX INSERTS





FEATURES & BENEFITS:

- Easy installation! Just peel and stick to inside of box.
- Can be installed before or after wall is closed.
- Non-conductive liner face.
- Easy retrofit installation.

reduced spacing.


- Low profile for minimum impact on box volume.
- Tested and proven acoustical properties.
- One step installation saves time and labor.



APPLICATIONS

- Single & multi-gang metallic boxes up to 14" (356 mm) long.
- Plastic & steel faceplates.
- 1 & 2 hr. wood or steel stud walls.







www.stifirestop.com