

Key Features & Benefits:

- Ballast Compatible & Line Voltage
- Double or Single Ended Power
- Food Safety Rated
- Up to 121 Lumens per Watt
- Internal Aluminum Heat Sink
- PET Housing
- Shatterproof Design



Project: _____

Date: _____

Catalog #: _____

Notes: _____

Technical Specifications:

Power: 15 Watts

Input Voltage: 100-277 VAC

Lumen Output: Up to 1,802 Lumens

Efficacy (lm/W): Up to 121 Lumens per Watt

Kelvin: 3500K, 4000K, 5000K

Color Rendering Index (CRI): >82

Housing Material: UL Fire Retardant PET

Rated Life (hrs): 50,000 Hours

Base Type: G13

Tube Dimensions (ØxL): 1.27" x 47.7"

Tube Weight (lbs): 0.5 Pounds



ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	CRI	QPL CODE
ESL-T8PBC-15W-F135	15W	1,727	116	3500K	>82	PSA2CGX8
ESL-T8PBC-15W-F140	15W	1,765	118	4000K	>82	PSR9YMYF
ESL-T8PBC-15W-F150	15W	1,802	121	5000K	>82	PX8CW72T

Ordering Guide:

Example Part Number: **ESL-T8PBC-15W-F135**

ESL	-	T8	-	PBC	-	15W	-	F	-	1	-	
ESL		T8		PBC		WATTS		LENS		GENERATION		KELVIN
		T8 Tube		Ballast Compatible		5W (15 Watts)		F (Frosted)		1 (1st Generation)		35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)

Key Features & Benefits:

- Ballast Compatible & Line Voltage
- Double or Single Ended Power
- Food Safety Rated
- Up to 121 Lumens per Watt
- Internal Aluminum Heat Sink
- PET Housing
- Shatterproof Design



Project: _____

Date: _____

Catalog #: _____

Notes: _____

Technical Specifications:

Power: 15 Watts

Input Voltage: 100-277 VAC

Lumen Output: Up to 1,802 Lumens

Efficacy (lm/W): Up to 121 Lumens per Watt

Kelvin: 3500K, 4000K, 5000K

Color Rendering Index (CRI): >82

Housing Material: UL Fire Retardant PET

Rated Life (hrs): 50,000 Hours

Base Type: G13

Tube Dimensions (ØxL): 1.27" x 47.7"

Tube Weight (lbs): 0.5 Pounds



ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	CRI	QPL CODE
ESL-T8PBC-15W-F135	15W	1,727	116	3500K	>82	PSA2CGX8
ESL-T8PBC-15W-F140	15W	1,765	118	4000K	>82	PSR9YMYF
ESL-T8PBC-15W-F150	15W	1,802	121	5000K	>82	PX8CW72T

Ordering Guide:

Example Part Number: **ESL-T8PBC-15W-F135**

ESL	-	T8	PBC	-	15W	-	F	1	
ESL		T8	PBC		WATTS		LENS	GENERATION	KELVIN
		T8 Tube	Ballast Compatible		5W (15 Watts)		F (Frosted)	1 (1st Generation)	35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)