

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EYD116 Drain Seal

Crouse-Hinds	
Catalog Number	EYD116
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eyd Conduit Sealing Fitting With Drain,
	Male and Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical
	Only, Group B Rated, 1/2"
Weight per unit	
Product Category	Sealing Bodies
Features	
connection	Female Threaded, Female Threaded
dimensions	1.2500 IN X 1.2500 IN X 3.2800 IN
Material, Color, and Finish	
Finish	Untreated
Descriptions	
Description	DRAIN SEAL
extra long description	CRS-H EYD116 1/2 NPT GRP B THRU MAL
Features	In addition to restricting the passage of gases, vapors or flames
	from one portion of the electrical installation to another,
	Crouse-Hinds series EYD and EZD drain sealing fittings prevent
	accumulation of condensate above the seal. They are installed in
	vertical conduit runs and at low points in conduit systems.
Long Description	Eaton Crouse-Hinds series EYD conduit sealing fitting with drain,
	Male and female, Feraloy iron alloy and/or ductile iron, Vertical
	only, Group B rated, 1/2"
Product Type	1/2 NPT GRP B Thru Male/Fem Iron Drain
Special Features	With Drain, Vertical Position
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274365169
Manufacturers Part Number	EYD116
UPC	782274365169
Taxonomies, Classifications, and C	Categories
Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit sealing fitting with drain
De also mino m	

Packaging

ckayırıy		
Carton	1	
Package	5	
Weight Per each	1.52	

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 2 Group F G, Class III
standard	UL 886, CSA C22.2