

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Packaging Carton

Weight Per each

EYS216SA EYS216SA 3/4 Al Cond Seal

Crouse-Hinds

Crouse-Hinds	
Catalog Number	EYS216SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Male and Female, Copper-Free Aluminum, Vertical or Horizontal, Group B Rated, 3/4"
Weight per unit	0.4300 (lbs/each)
Product Category	Aluminum
Features	
connection	Male Threaded, Female Threaded
dimensions	1.5000 IN X 1.5000 IN X 3.6900 IN
Descriptions	
Description	EYS216SA 3/4 AL COND SEAL
extra long description	CRS-H EYS216 SA 3/4 NPT MALE/FEM AL
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings
	restrict the passage of gases, vapors or flames from one portion
	of the electrical installation to another, limit explosions to the
	sealed off enclosure, and limit pre-compression or "pressure
	piling" in conduit systems. EYS sealing fittings are available for
	installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including
	Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Male and
20.1g 2 000.1p 1.0.1	female, Copper-free aluminum, Vertical or horizontal, Group B rated, 3/4"
Product Type	3/4 NPT Male/Fem Al Vert/Horz Seal FTG
Special Features	Horizontal/Vertical Position
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274380216
Manufacturers Part Number	EYS216 SA
UPC	782274380216
Taxonomies, Classifications, and (Categories
Category Description	LIAZADDOLIC LOCATION FITTINGS
Туре	

5

0.43

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2