

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EYS21SA 3/4 Al Cond Seal Crouse-Hinds

Catalog Number	EYS21SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Female, Copper-Free Aluminum, Vertical or Horizontal, Group B Rated, 3/4"
Weight per unit	0.0620 (lbs/each)
Product Category	Aluminum
Features	
connection	Male Threaded, Female Threaded
dimensions	1.5000 IN X 1.5000 IN X 3.6900 IN
Descriptions	
Description	3/4 AL COND SEAL
extra long description	CRS-H EYS21 SA 3/4 NPT THRU FEM AL
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Female, Copper-free aluminum, Vertical or horizontal, Group B rated, 3/4"
Product Type	2/4 NDT Thru Fom ALVort/Horz Soal FTC
Special Features	Horizontal/Vertical Position
Vanufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274275840
Manufacturers Part Number	EYS21 SA
UPC	782274275840
Taxonomies, Classifications, and (Categories
Category Description	
Туре	Conduit sealing fitting
Packaging	
Carton	
Package	
Weight Per each	0.062



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2