


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





EYS3 1" Male & Female Hub Vertical Seal Off *Crouse-Hinds*

Crouse-Hinds	
Catalog Number	EYS3
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical Only, Group B Rated, 1"
Weight per unit	2.0 (lbs/each)
Product Category	Sealing Bodies
eatures	
connection	Female Threaded, Female Threaded
dimensions	1.7500 IN X 1.7500 IN X 4.3100 IN
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Descriptions	
Description	1" MALE & FEMALE HUB VERTICAL SEAL OFF
extra long description	CRS-H EYS3 1 NPT THRU FEMALE CST IR
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Female, Feraloy iron alloy and/or ductile iron, Vertical only, Group B rated, 1"
Product Type	1 NPT Thru Female CST Iron Vert Seal FTG
Special Features	
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274377605
Manufacturers Part Number	EYS3
UPC	782274377605

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	Conduit sealing fitting



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

				•	
110	\sim 1	<i>,</i> ~		1	•
Pa		•			ш
·	v	ľ	M.		

Carton	2	
Package	20	
Weight Per each	1.98	

Uses, Certifications, and Standards

•	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
	Div 2 Group F G, Class III
standard	UL 886, CSA C22.2