



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3737 Grader Street Suite 120
75041-0000, TX Garland
Phone: 214-503-7227
Fax: 214-503-9766



EYS51 1-1/2" Male & Female Hub Vert/Horizontal Seal Off *Crouse-Hinds*

Catalog Number	EYS51
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical or Horizontal, Group B Rated, 1-1/2"
Weight per unit	3.5 (lbs/each)
Product Category	Sealing Bodies

Features

connection	Female Threaded, Female Threaded
dimensions	2.4400 IN X 2.4400 IN X 5.5000 IN

Material, Color, and Finish

Finish	Electrogalvanized With Aluminum Acrylic Painted
--------	---

Descriptions

Description	1-1/2" MALE & FEMALE HUB VERT/HORIZONTAL SEAL OFF
extra long description	CRS-H EYS51 1 1/2 NPT FEM CST IRON
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings restrict the passage of gases, vapors or flames from one portion of the electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYS sealing fittings are available for installation in either vertical only or in both horizontal or vertical positions. They are available in a variety of materials, including Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Female, Feraloy iron alloy and/or ductile iron, Vertical or horizontal, Group B rated, 1-1/2"
Product Type	1 1/2 NPT Fem CST Iron Vert/Horz Seal FT
Special Features	Horizontal/Vertical Position

Manufacturer Information

Brand	Eaton
GTIN	00782274379302
Manufacturers Part Number	EYS51
UPC	782274379302

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	Conduit sealing fitting



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3737 Grader Street Suite 120
75041-0000, TX Garland
Phone: 214-503-7227
Fax: 214-503-9766

Packaging

Carton 2

Weight Per each 3.53

Uses, Certifications, and Standards

Application Ind Facilities & Factories - Industrial Facilities/Factories - Other

Enclosure Class I Div 1 2 Group B C D, Class II Div 1 2 Group E F G, Class III

standard UL 886, CSA C22.2