

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



EYSR5 1-1/2" Cond Seal Crouse-Hinds

Catalog Number	EYSR5
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eysr Retrofit Sealing Fitting, Feraloy Iron Alloy, 1-1/2"
Weight per unit	
Product Category	

Features

dimensions 5.2500 IN X 3.0000 IN X 3.6300 IN FERALOY IRON ALLOY Material

Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

Dimensions and Weight

1-1/2 in Size

Descriptions

Construction	Explosionproof, Dust Ignitionproof
Description	1-1/2" COND SEAL
extra long description	CRS-H EYSR5 1 1/2 RETROFIT SEAL FT
Features	Crouse-Hinds series EYSR retrofit sealing fittings are installed in rigid metal conduit systems in Class I, Division 2 hazardous locations to replace installed Eaton's Crouse-Hinds series EYS or EYD sealing fittings. EYSRs allow the replacement to be done without disassembly of the conduit system, and they can be installed in vertical or horizontal positions, indoors or outdoors. As with all sealing fittings, EYSRs restrict the passage of gases, vapors or flames from one portion of the electrical install
Long Description	Eaton Crouse-Hinds series EYSR retrofit sealing fitting, Feraloy iron alloy, 1-1/2"
Product Type	1 1/2 Retrofit Seal FT 5 1/4 X 3 5/8 X 3
Special Features	Horizontal/Vertical Position

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274793412
Manufacturers Part Number	EYSR5
UPC	782274793412

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Retrofit sealing fitting



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

D I	
Packag	ıına
	, ,

Carton	1	
Weight Per each	6.85	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 2 Group E F G
standard	UL 886, CSA C22.2