

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### EYSX11 1/2" Female Cond Seal

EYSX11
Crouse-Hinds
Eaton Crouse-Hinds Series Eysx Expanded Fill Sealing Fitting, Female, Feraloy Iron Alloy, Vertical or Horizontal, Group B Rated, 1/2"
1.3 (lbs/each)
Sealing Bodies
Female Threaded, Female Threaded
1.5000 IN X 1.5000 IN X 3.6900 IN
Electrogalvanized With Aluminum Acrylic Painted
1/2" FEMALE COND SEAL
CRS-H EYSX11 1/2 FEM VERT/HORZ EXPA
EYSX expanded fill sealing fittings from Eaton Crouse-Hinds Division provide 40% wire fill capacity to allow uninterrupted runs in a conduit system. They are designed to restrict the passage of gases, vapors or flames from one portion of the

electrical installation to another, limit explosions to the sealed off enclosure, and limit pre-compression or "pressure piling" in conduit systems. EYSX expanded fill sealing fittings are available for installation in both horizontal or vertical positions. Eaton Crouse-Hinds series EYSX expanded fill sealing fitting, **Long Description** Female, Feraloy iron alloy, Vertical or horizontal, Group B rated, 1/2" **Product Type** 1/2 Fem Vert/Horz Expand Fill Sealing FT Special Features Horizontal/Vertical Position

#### **Manufacturer Information**

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274943169
Manufacturers Part Number	EYSX11
UPC	782274943169

#### **Taxonomies, Classifications, and Categories**

Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Expanded fill sealing fitting



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pac	kag	ıng
-----	-----	-----

Carton	1	
Weight Per each	1.26	

#### Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group B C D, Class Ii Div 1 2 Group E F G, Class Iii
standard	UL 886, CSA C22.2