

41891 - F96T8/XL/SP41

GE Starcoat® T8

• Provides significantly longer life than standard lamp helping to reduce maintenance costs





CAUTIONS & WARNINGS

Caution


- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning


- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS


Graphs_Spectral Power Distribution



Graphs_Lumen Maintenance



Graphs_Lamp Mortality



GENERAL CHARACTERISTICS

Lamp Type

Bulb Base Rated Life Rated Life (instant start) @ Time Bulb Material Starting Temperature (MIN) LEED-EB MR Credit Linear Fluorescent - Straight Linear T8 Single Pin (Fa8) 24000. hrs 24000 h @ 3 h 30000 h @ 12 h Soda lime 10.0 °C 682 picograms Hg per mean lumen hour Full Wattage

Primary Application

PHOTOMETRIC CHARACTERISTICS

Initial Lumens5800.0Mean Lumens5500.0Nominal Initial Lumens per Watt98Color Temperature4100.0 KColor Rendering Index (CRI)78.0

ELECTRICAL CHARACTERISTICS

Wattage59.0Cathode Resistance Ratio - Rh/4.25Rc (MIN)Cathode Resistance Ratio - Rh/6.5Rc (MAX)Current Crest Factor (MAX)1.7

DIMENSIONS

Maximum Overall Length 96.0000 in(2438.4 mm) (MOL) Minimum Overall Length 93.7400 in(2381.0 mm) Nominal Length 96.000 in(2438.4 mm) Bulb Diameter (DIA) (MIN) 0.940 in(23.9 mm) Bulb Diameter (DIA) (MAX) 1.100 in(27.9 mm) Bulb Diameter (DIA) 1.000 in(25.4 mm) Face to End of Opposing Pin 93.420 in(2372.9 mm) (B) (MIN) Face to End of Opposing Pin 93.500 in(2374.9 mm) (B) (MAX)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168418911