Eaton FAZ-C50{}2-NA

Catalog Number: FAZ-C50/2-NA

Eaton FAZ branch protector,UL 489 Industrial miniature circuit breaker - supplementary protector,Medium levels of inrush current are expected,50 A,10 kAIC,Two-pole,240 V,5-10X /n,50-60 Hz,Screw terminals,C Curve



Photo is representative

General specifications

Product Name Eaton FAZ branch protector UPC 786689042387 Product Height 1.5 in Product Weight 0.5 lb Certifications UL 489

Catalog Number FAZ-C50/2-NA Product Length/Depth 1.4 in Product Width 3 in

Warranty 1 year

Powering Business Worldwide

Physical Attributes

Number of poles

Two-pole

Terminals

Screw

Туре

UL 489 Industrial miniature circuit breaker - supplementary protector

Performance Ratings

Amperage Rating

50 A

Circuit protection

C curve

Frequency rating

50-60 Hz

Interrupt rating 10 kAIC

Тгір Туре

5-10X /n

Voltage rating

277/480V

Miscellaneous

Application

Suitable for applications where medium levels of inrush current are expected

Resources

Catalogs UL 489 DIN rail miniature circuit breakers

Specifications and datasheets Eaton Specification Sheet - FAZ-C50/2-NA



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia

Eaton FAZ-C50{}2-NA

Catalog Number: FAZ-C50/2-NA

Eaton FAZ branch protector,UL 489 Industrial miniature circuit breaker - supplementary protector,Medium levels of inrush current are expected,50 A,10 kAIC,Two-pole,240 V,5-10X /n,50-60 Hz,Screw terminals,C Curve



Photo is representative

General specifications

Product Name Eaton FAZ branch protector UPC 786689042387 Product Height 1.5 in Product Weight 0.5 lb Certifications UL 489

Catalog Number FAZ-C50/2-NA Product Length/Depth 1.4 in Product Width 3 in

Warranty 1 year

Powering Business Worldwide

Physical Attributes

Number of poles

Two-pole

Terminals

Screw

Туре

UL 489 Industrial miniature circuit breaker - supplementary protector

Performance Ratings

Amperage Rating

50 A

Circuit protection

C curve

Frequency rating

50-60 Hz

Interrupt rating 10 kAIC

Тгір Туре

5-10X /n

Voltage rating

277/480V

Miscellaneous

Application

Suitable for applications where medium levels of inrush current are expected

Resources

Catalogs UL 489 DIN rail miniature circuit breakers

Specifications and datasheets Eaton Specification Sheet - FAZ-C50/2-NA



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia