

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FD3 1G Dev Box

Crouse-Hinds	
Catalog Number	FD3
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FD Device Box, Deep, Feraloy Iron Alloy, Single-Gang, 1"
Weight per unit	
Product Category	FS & FD Type Boxes & Covers
Features	
Cable Entry	(1) End
dimensions	5.2800 IN X 2.6900 IN X 2.7500 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron Alloy
Dimensions and Weight Size	1 in
Descriptions	
Description	1G DEV BOX
extra long description	CRS-H FD3 1 NPT DE IRON FD BX SGL G
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FD device box, Deep, Feraloy

Manufacturer Information

Product Type **Special Features**

Brand	Eaton
GTIN	00782274397009
UPC	782274397009

iron alloy, Single-gang, 1"

Depth X 5-9/32 In Height

1 NPT De Iron FD BX SGL GNG MTG Lugs

Configuration Type FD, Dimension 2-3/4 In Width X 2-11/16 In

Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Type	DEVICE BOX



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Package	2
Weight Per each	3.38
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	FLUSH

UL 514, CSA C22.2, Federal Specification W-C-5860