

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Packaging Carton

Weight Per each

FP30118BLACK100 Thin-Wall Heat Shrink Tubing, BK, 100'

Catalog Number	FP30118BLACK100
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Tubing FP-301 Is A General Purpose, Thin Wall Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection.
Weight per unit	0.0024 (lbs/each)
Product Category	Insulating Materials
scriptions	
Description	THIN-WALL HEAT SHRINK TUBING, BK, 100'
extra long description	3M FP0.125BK100'S FP-SM 1/8 BK SPL
Features	3M™ Heat Shrink Tubing FP-301 is color-coded for quick and easidentification of the wire. This split-resistant, flame-retardant tubing is used as shrink-fit, electrical insulation over cable splice or terminations. The high-expansion-ratio tubing is mechanically tough, easily markable and resists cold flow. It is perfect for lightweight wire-harness covering, fire-resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of -67 to 275 degrees F (-55 to 135 degre
Long Description	3M™ Heat Shrink Tubing FP-301 is a general purpose, thin wall tubing that provides a balance of electrical, physical and chemic properties, making it ideal for industrial and military application This tubing has a 2:1 shrink ratio and provides flame retardant insulation for 600V rated applications. It has a flexible polyolefin construction that offers moisture seal protection.
Product Type	FP-SM 1/8 BK SPL 100 Feet 3300125BK 300F
nufacturer Information	
Brand	3M
GTIN	00076308624118
Manufacturers Part Number	FP0.125BK100'S
UPC	076308624118

300

0.0024