

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FP30134X200CLEAR Heat Shrink Thin-Wall Tubing FP-301-3/4-Clear-200' Minnesota Mining (3M)

Catalog Number	FP30134X200CLEAR
Manufacturer	Minnesota Mining (3M)
Description	3M™ Heat Shrink Tubing FP-301 Is A General Purpose, Thin Wall Tubing That Provides A Balance Of Electrical, Physical and Chemical Properties, Making It Ideal For Industrial and Military Applications. This Tubing Has A 2:1 Shrink Ratio and Provides Flame Retardant Insulation For 600V Rated Applications. It Has A Flexible Polyolefin Construction That Offers Moisture Seal Protection.
Weight per unit	4.8 (lbs/each)
Product Category	Insulating Materials
Features	
continuous operating temperat	-67 degrees to 275 degrees
Dielectric Strength	900
flammability	Pass
Inside Diameter	0.375
outside diameter	0.75
Shrink Ratio	2:1
Material, Color, and Finish	
Color	Colorless
Dimensions and Weight Length	2400
Thickness	0.03



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_	•		
11000	rin	TIAR	•
Desc			17
-			

Description	HEAT SHRINK THIN-WALL TUBING FP-301-3/4-CLEAR-200'
extra long description	3M FP0.750CR200'L FP 3/4 CR SPL
Features	3M™ Heat Shrink Tubing FP-301 is color-coded for quick and easy identification of the wire. This split-resistant tubing is used as shrink-fit, electrical insulation over cable splices or terminations. The high-expansion-ratio tubing is mechanically tough, easily markable and resists cold flow. It is perfect for lightweight wire-harness covering, fire-resistant covering, wire marking, wire bundling and component packaging. It withstands temperatures of -67 to 275 degrees F (-55 to 135 degrees C). SAE-AMS-DT
Long Description	3M™ Heat Shrink Tubing FP-301 is a general purpose, thin wall tubing that provides a balance of electrical, physical and chemical properties, making it ideal for industrial and military applications. This tubing has a 2:1 shrink ratio and provides flame retardant insulation for 600V rated applications. It has a flexible polyolefin construction that offers moisture seal protection.
Product Type	FP 3/4 CR SPL 5300750CR
Special Features	Flexible, Polyolefin
nufacturer Information	
Brand	3M

Mar

Brand	3M	
GTIN	00054007085317	
Manufacturers Part Number	FP0.750CR200'L	
UPC	054007085317	

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Туре	Single (Thin) Wall

Availability

minimum qty	200
	 8.8

Packaging

Carton	200
Weight Per each	4.8

Uses, Certifications, and Standards

standard	UL, CSA, ABS
5.57051505	