

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRNR175 175A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

Т	
Catalog Number	FRNR175
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FRN-R Fuse, 175 A, Dual, Class RK5, Non-Indicating, Blade End X Blade End, 10 Sec At 500%, 20 Kaic At 125 VDC, 200 Kaic At 250 V, Standard, 250 V, 125 VDC
Weight per unit	0.8100 (lbs/each)
Product Category	
eatures	
amperage rating	175 A
class	Class RK5
connection	Blade End X Blade End
dimensions	2.0000 IN X 0.5600 IN X 0.5600 IN
element	B 1
interrupt rating	20 kAIC at 125 Vdc200 kAIC at 250 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	250 VAC, 125 VDC
imensions and Weight	
Size	1.56 In Diameter X 7.13 In Length
escriptions	
Description	175A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-175 FUSETRON DUAL-ELEMEN
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500% of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann series FRN-R fuse, 175 A, Dual, Class RK5, Non-indicating, Blade end x blade end, 10 sec at 500%, 20 kAIC at 250 Vdc,200 kAIC at 250 V, Standard, 250 V, 125 Vdc
Product Type	Fusetron Dual-Element Class RK5



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

N	1000	faatii	rar Ind	Fa	+100
I١	/ianui	iactu	rer ini	forma	uon

Brand	Eaton	
GTIN	00051712507479	
Manufacturers Part Number	FRN-R-175	
UPC	051712507479	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

onagg	
Carton	1
Weight Per each	0.81

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked