

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRNR7 7A 250V TD Class RK5 Dual Elem Fuse-Fusetron

Bussmann Fuses

Catalog Number	FRNR7
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FRN-R Fuse, 7 A, Dual, Class RK5, Non-Indicating, Ferrule End X Ferrule End, 8 Sec At 500%, 200 Kaic At 250 V, 20 Kaic At 125 VDC, Standard, 250 V, 125 VDC
Weight per unit	
Product Category	Dual Element
atures	
amperage rating	7 A
class	Class RK5
connection	Ferrule End X Ferrule End
dimensions	2.0000 IN X 0.5600 IN X 0.5600 IN
element	Dual
interrupt rating	20 kAIC at 125 Vdc200 kAIC at 250 Vac
media	
Response Time	
Voltage Rating	250 VAC, 125 VDC
nensions and Weight	
Size	0.56 In Diameter X 2.00 In Length
scriptions	
Description	7A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-7 FUSETRON DUAL-ELEMENT
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes
Long Description	Eaton Bussmann series FRN-R fuse, 7 A, Dual, Class RK5, Non-indicating, Ferrule end x ferrule end, 8 sec at 500%, 200 kA at 250 V,20 kAIC at 125 Vdc, Standard, 250 V, 125 Vdc
Product Type	Fusetron Dual-Element Class RK5
nufacturer Information	
Brand	Eaton
GTIN	00051712507257
Manufacturers Part Number	FRN-R-7
UPC	051712507257



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.06
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	Contact factory,CE Marked