

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**Product Type** 

### FRNR80 80A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

Dussinami uses	
Catalog Number	FRNR80
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FRN-R Fuse, 80 A, Dual, Class RK5, Non-Indicating, Blade End X Blade End, 10 Sec At 500%, 200 Kaic At 250 V, 20 Kaic At 125 VDC, Standard, 250 V, 125 VDC
Weight per unit	0.3200 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	80 A
class	Class RK5
connection	
dimensions	3.0000 IN X 0.8100 IN X 0.8100 IN
element	D I
interrupt rating	200 kAIC at 250 Vac20 kAIC at 125 Vdc
media	Yes
Response Time	
Voltage Rating	250 VAC, 125 VDC
<b>Dimensions and Weight</b>	
Size	1.06 In Diameter X 5.88 In Length
Descriptions	
Description	80A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-80 FUSETRON DUAL-ELEMENT
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500% of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann series FRN-R fuse, 80 A, Dual, Class RK5, Non-indicating, Blade end x blade end, 10 sec at 500%, 200 kAIC at 250 V,20 kAIC at 125 Vdc, Standard, 250 V, 125 Vdc
D. J. J. T	F l D l Fl l Ol DVF

Fusetron Dual-Element Class RK5



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и	•	IABLIT	· ^ ^ †	COLID	forma	STIAN
•	•	141111	41 1111	~		4116311

Brand	Eaton
GTIN	00051712507417
Manufacturers Part Number	FRN-R-80
UPC	051712507417

## **Taxonomies, Classifications, and Categories**

Category Description	Fuses & Fuse Accessories
Type	FUSF

## **Packaging**

3 - 3	
Carton	5
10.11.11.00	
Weight Per each	0.32

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked