

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRSR300_300A 600V TD Class RK5 Dual Elem Fuse-Fusetron

Bussmann Fuses

Catalog Number	FRSR300
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FRS-R Fuse, 300 A, Dual, Class RK5, Non-Indicating, Blade End X Blade End, 10 Sec At 500%, 20 Kaic At 300 VDC, 200 Kaic At 600 V, Standard, 600 V, 300 VDC
Weight per unit	2.3 (lbs/each)
Product Category	
atures	
amperage rating	300 A
class	
connection	
dimensions	
element	Dual
interrupt rating	20 kAIC at 300 Vdc200 kAIC at 600 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
mensions and Weight	
Size	2.34 In Diameter X 11.63 In Length
escriptions	
Description	300A 600V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRS-R-300 FUSETRON DUAL ELEMEN
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) o time-delay at 500% of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann series FRS-R fuse, 300 A, Dual, Class RK5, Non-indicating, Blade end x blade end, 10 sec at 500%, 20 kAIC 300 Vdc,200 kAIC at 600 V, Standard, 600 V, 300 Vdc
	500 Vuc,200 KAIC at 000 V, Standard, 000 V, 500 Vuc
Product Type	Fusetron Dual Element Fuse Class RK5



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00051712508513
Manufacturers Part Number	FRS-R-300
UPC	051712508513
Taxonomies, Classifications, and Cat	egories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	1
Weight Per each	2.34
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked