



## FRSR600 600A 600V TD Class RK5 Dual Elem Fuse-Fusetron

*Bussmann Fuses*

Catalog Number	FRSR600
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRS-R, Time-Delay, Dual-Element, Current Limiting Fuse, 600 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 600 Vac and 20 Ka At 300 VDC
Weight per unit	3.6 (lbs/each)
Product Category	Dual Element

### Features

amperage rating	600
connection	Blade End X Blade End
dimensions	13.3800 IN X 2.8800 IN X 2.8800 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	200 kAIC at 600 Vac20 kAIC at 300 Vdc
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

### Dimensions and Weight

Size	2.88 In Diameter X 13.38 In Length
------	------------------------------------

### Descriptions

Description	600A 600V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRS-R-600 FUSETRON DUAL ELEMEN
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay, dual-element, current limiting fuse, 600 A, non-indicating fuse, interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc
Product Type	Fusetron Dual Element Fuse Class RK5
Special Features	Renewable



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

320 SW 28TH ST  
72712-0000, AR Bentonville  
Phone: 479-250-1930  
Fax: 479-250-1931

## Manufacturer Information

Brand	Eaton
GTIN	00051712508568
Manufacturers Part Number	FRS-R-600
UPC	051712508568

## Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

## Packaging

Carton	1
Weight Per each	3.62

## Uses, Certifications, and Standards

Application standard	Ind Facilities & Factories - Facility: Safety and Security Systems CE Marked
----------------------	---