

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## FSC1 1G FS-Dev Box, 1/2" Crouse-Hinds

Catalog Number	FSC1
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FS Device Box, Shallow,
	Feraloy Iron Alloy, Single-Gang, C Shape, 1/2"
Weight per unit	2.6 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

#### **Features**

Cable Entry	(1) Each End
dimensions	6.0300 IN X 1.8800 IN X 2.7500 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron
	Allov

#### **Dimensions and Weight**

^:	1 10 1
Size	1/2 in
.11715	1// 111
0120	

#### **Descriptions**

Description	1G FS-DEV BOX, 1/2"
extra long description	CRS-H FSC1 1/2 THRUFEED CST IRON BX
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FS device box, Shallow, Feraloy iron alloy, Single-gang, C shape, 1/2"
Product Type	1/2 Thrufeed CST Iron BX SGL GNG MT Lug
Special Features	Configuration Type FSC, With Mounting Lug and Ground Screw, Dimension 2-3/4 In Width X 1-7/8 In Depth X 6-1/32 In Height

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274410302
Manufacturers Part Number	FSC1
UPC	782274410302

### **Taxonomies, Classifications, and Categories**

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX



Mounting

standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

FLUSH

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	5
Weight Per each	2.55
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other

UL 514, CSA C22.2, Federal Specification W-C-5860