

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FSD212 2G FSD-Box

Crouse-Hinds

Catalog Number	FSD212
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FS Device Box, Shallow,
	Feraloy Iron Alloy, Two-Gang, D Shape, 3/4"
Weight per unit	3.6 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

Features

Cable Entry	(2) One End, (1) Other End
dimensions	4.6300 IN X 1.6900 IN X 6.0600 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron
	Alloy

Dimensions and Weight

Size	3/4 in	
------	--------	--

Descriptions

criptions	
Description	2G FSD-BOX
extra long description	CRS-H FSD212 3/4 NPT IRON FS BX TWO
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FS device box, Shallow, Feraloy iron alloy, Two-gang, D shape, 3/4"
Product Type	3/4 NPT Iron FS BX Two GNG MTG Lugs
Special Features	Configuration Type FSD, With Mounting Lug, Dimension 4-5/8 In Width X 1-7/8 In Depth X 6-1/16 In Height

Manufacturer Information

Brand	Eaton
GTIN	00782274415208
Manufacturers Part Number	FSD212
UPC	782274415208

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Туре	DEVICE BOX



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

a				

Carton	1
Weight Per each	3.6

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	SURFACE
standard	UL 514, CSA C22.2, Federal Specification W-C-5860