

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FSS1 FS Box Crouse-Hinds

Catalog Number	FSS1
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FS Device Box, Shallow, Feraloy Iron Alloy, Single-Gang, S Shape, 1/2"
Weight per unit	
Product Category	FS & FD Type Boxes & Covers
atures	
Cable Entry	(1) End
dimensions	5.1600 IN X 1.8800 IN X 2.7500 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron Alloy
mensions and Weight	
Size	1/2 in
escriptions	
Description	FS BOX
extra long description	CRS-H FSS1 1/2 FS &FD SGL GANG CAST
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, huk configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FS device box, Shallow, Feraloy iron alloy, Single-gang, S shape, 1/2"
Product Type	1/2 FS &FD SGL Gang Cast Device BX
Special Features	Configuration Type FSS, With Mounting Lug, Dimension 2-3/4 I Width X 1-7/8 In Depth X 5-5/32 In Height
anufacturer Information Brand	Eaton
GTIN	00702274410605
Manufacturers Part Number	FSS1
UPC	782274418605

Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Package	5
Weight Per each	2.34

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	SURFACE
standard	UL 514, CSA C22.2, Federal Specification W-C-5860