

ELLIOTT ELECTRIC SUPPLY 5150 N. Hwy 81 73533-0000, OK Duncan Phone: 580-252-2582 Fax: 580-252-2738



FSS2 1G FS-Dev Box, 3/4" Crouse-Hinds

Catalog Number	FSS2
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FS Device Box, Shallow,
	Feraloy Iron Alloy, Single-Gang, S Shape, 3/4"
Weight per unit	2.2 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

Features

Cable Entry	(1) End
dimensions	5.1600 IN X 1.8800 IN X 2.7500 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron
	Alloy

Dimensions and Weight

Size	3/4 in
SIZE	J/ 4 II I

Descriptions

Description	1G FS-DEV BOX, 3/4"
extra long description	CRS-H FSS2 3/4 FS/FD SGL CAST DEVIC
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FS device box, Shallow, Feraloy iron alloy, Single-gang, S shape, 3/4"
Product Type	3/4 FS/FD SGL Cast Device BX
Special Features	Configuration Type FSS, With Mounting Lug, Dimension 2-3/4 In Width X 1-7/8 In Depth X 5-5/32 In Height

Manufacturer Information

Brand	Eaton
GTIN	00782274418704
Manufacturers Part Number	FSS2
UPC	782274418704



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5150 N. Hwy 81 73533-0000, OK Duncan Phone: 580-252-2582 Fax: 580-252-2738

Taxonomies, Classifications, and Cate	
Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX
Packaging	
Carton	1
Package	5
Weight Per each	2.16
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	SURFACE
standard	UL 514, CSA C22.2, Federal Specification W-C-5860