

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



G1.5X2WH6 SLTD Wiring Duct *Panduit Corporation*

Catalog Number	G1.5X2WH6
Manufacturer	Panduit Corporation
Description	The G1.5X2WH6 Panduct Lead-Free PVC Wide Slot Wiring Duct Feature A Wide Slot/Finger Design That Provides Greater Sidewall Rigidity and Is Suitable With A Range Of Wire Bundle Sizes. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). Mounting Holes Provided. 1.5" X 2.0" (38.1 MM X 50.8 MM) and 6' (1.8 M) Long. Cover Sold Separately. Color White.
Weight per unit	
Product Category	
Features	Daois/naosnays/namajs/nay
connection	Mounting Holes
Material	PVC
media	Yes
Material, Color, and Finish	
Color	White
Dimensions and Weight	
Length	6.00
Size	1.75 x 2.12
Width	1.75
Descriptions	
Description	SLTD WIRING DUCT
extra long description	PAN G1.5X2WH6 Panduct® G1.5X2WH6 Ba
Long Description	The G1.5X2WH6 Panduct Lead-Free PVC Wide Slot Wiring Duct feature a wide slot/finger design that provides greater sidewall rigidity and is suitable with a range of wire bundle sizes. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. 1.5' x 2.0" (38.1 mm x 50.8 mm) and 6' (1.8 m) long. Cover sold separately. Color White.
Product Type	Panduct® G1.5X2WH6 Base Wiring Duct
Manufacturer Information	
Brand	PANDUIT
GTIN	00074983546183
Manufacturers Part Number	G1.5X2WH6
UPC	074983546183



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	WIRE DUCT AND COVERS
Туре	Base Wiring Duct
Packaging	
Carton	120
Weight Per each	0.0114
Uses, Certifications, and Standards	
Application	Wide slot/finger design provides greater sidewall rigidity and can
	be used in a wide range of applications

RoHS Compliant, UL Recognized, CE Compliant; CSA Approved