

GAR2126, Mechanical Grounding Connector, Cable to Rod or Pipe

By Burndy Catalog # GAR2126

Mechanical Grounding Connector, Cable to Rod or Pipe, 4 AWG (Sol.) - 2/0 AWG (Str.), 3-1/2" to 4" Rod, 3-1/2" Pipe, Bright Dipped.



Application

For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Direct Burial Cable, Fence Post

General

EU RoHS Indicator Yes

Installation Torque 240 LBS/in

Recommended in-lb

Material Copper Alloy

Material - Hardware DURIUM™ Silicon Bronze

Plated

Plating Type **Bright Dipped**

Sub Brand MECHANICAL CONNECTOR

Type GAR 264 U Bolt Type

UPC 781810236802 UPC 12 Digit 7818102368022

Dimensions

4.00 in Dimension - B Length inch 6-1/4 in Dimension - Height fraction Dimension - Height inch 6.25 in Dimension - L Length Overall 40 mm 1.56 in Dimension - Length Overall inch Dimension - Outside Diameter 4.00 in Dimension - Width fraction 5-3/8 in Dimension - Width inch 5.31 in Dimension - Width mm 135 mm

Conductor Related

Conductor - Copper Solid Size 4 AWG;3 AWG;2 AWG;1

AWG;1/0 AWG;2/0 AWG;3/0

AWG

Conductor - Copper Solid Size 4 AWG-2/0 AWG

Range

5 AWG;4 AWG;3 AWG;2 Conductor - Copper Str Size

AWG;1 AWG;1/0 ;2/0 AWG

5 AWG-2/0 AWG

Conductor - Copper Str Size

Range

Conductor - Copper Tube Std 3 1/2 IPS IPS

Conductor - Copper Tube Std 3 1/2 IPS IPS

Size Range

Conductor - Pipe or Round

Tube Size

Conductor - Rod Size

Conductor Type

3.5 - 4.0 in

3 1/2 in

• CU C Solid-Size

• CU C Str-Size

• CU Tube Std-Size

Rod-Size

UL467

Certifications and Compliance

Certification - CSA Approved Certification - ETL No Certification - UL Listed Direct Yes Burial Certification - UL Recognized No Certification - cULus No Industry Standard(s) **UL467**

Standards - Industry Standards Met

Standards - RoHS Compliance EX

Status

UL Listed Yes

Logistics

Minimum Pack Quantity

Product Assets

3D Models - GAR2126 MODEL-PDF 3D Models - GAR2126 MODEL-IGES 3D Models - GAR2126_MODEL-STEP Customer Notices - Prop 65 Notice Sales Drawings - SD..015789-01

