

GAR2229, Mechanical Grounding Connector, Cable to Rod or Pipe

By Burndy Catalog # GAR2229

Mechanical Grounding Connector, Cable to Rod or Pipe, 2/0 AWG (Sol) -250 kcmil, 4" Pipe, 4"-4-1/2" Rod, Bright Dipped.



Application

For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Direct Burial Cable, Fence Post

General

EU RoHS Indicator Yes

Installation Torque 240 LBS/in

Recommended in-lb

Material Copper Alloy

Material - Hardware DURIUM™ Silicon Bronze

Plated

Plating Type **Bright Dipped**

Sub Brand MECHANICAL CONNECTOR

Type GAR 261 U Bolt Type

UPC 781810237601 UPC 12 Digit 7818102376011

Dimensions

4.50 in Dimension - B Length inch 6-3/8 in Dimension - Height fraction Dimension - Height inch 6.38 in Dimension - L Length Overall 46 mm 1.81 in Dimension - Length Overall inch Dimension - Outside Diameter 4.50 in Dimension - Width fraction 5-7/8 in Dimension - Width inch 5.81 in Dimension - Width mm 148 mm

Conductor Related

Conductor - Copper Solid Size 2/0 AWG;3/0 AWG;4/0 AWG

Conductor - Copper Solid Size 2/0 AWG-250 Kcmil

Range

1/0;2/0 AWG;3/0 AWG;4/0 Conductor - Copper Str Size

> AWG;250 kcmil 1/0 -250 kcmil

Conductor - Copper Str Size

Range

Conductor - Copper Tube Std 4 IPS IPS

Conductor - Copper Tube Std 4 IPS IPS

Size Range

Conductor - Pipe or Round 4 in

Tube Size

Conductor - Rod Size 4.0 - 4.5 in

Conductor Type • CU C Solid-Size

• CU C Str-Size

• CU Tube Std-Size

Rod-Size

Certifications and Compliance

Certification - CSA Approved Certification - ETL No Certification - UL Listed Direct Yes Burial Certification - UL Recognized Certification - cULus No **UL467** Industry Standard(s) Standards - Industry **UL467** Standards Met Standards - RoHS Compliance Status

UL Listed

Yes

Logistics

Minimum Pack Quantity

Product Assets

3D Models - GAR2229_MODEI-PDF 3D Models - GAR2229_MODEL-IGES 3D Models - GAR2229 MODEL-STEP Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SD..015789-01