



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## GASK805N 1-1/2 Neo Body GS

*Crouse-Hinds*

Catalog Number	GASK805N
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 8 Gasket, Neoprene, 1-1/2", Open
Weight per unit	0.0400 (lbs/each)
Product Category	Bodies & Covers

### Features

connection	Water Jet Cut
dimensions	2.8100 IN X 0.0600 IN X 7.9400 IN
Material	Neoprene

### Material, Color, and Finish

Color	Black
Finish	Black

### Descriptions

Description	1-1/2 NEO BODY GS
extra long description	CRS-H GASK805N 1 1/2 OPEN NEO FORM
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 8 bodies are offered in seven different shapes to provide the most flexible offering on the market. Form 8 Condulet outlet bodies provide more room for heavier conductors. Many shapes and sizes are available for rigid threaded conduit. Two cover screws on all body sizes provide tight
Long Description	Eaton Crouse-Hinds series Condulet Form 8 gasket, Neoprene, 1-1/2", Open
Product Type	1 1/2 Open Neo Form 8 Gask

### Manufacturer Information

Brand	Eaton
GTIN	00782274098586
Manufacturers Part Number	GASK805N
UPC	782274098586

### Taxonomies, Classifications, and Categories

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Type	Gasket



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Availability

Status ..... Inactive .....

## Packaging

Carton ..... 1 .....

Package ..... 25 .....

Weight Per each ..... 0.04 .....

## Uses, Certifications, and Standards

Application ..... Ind Facilities & Factories - Industrial Facilities/Factories - Other .....

standard ..... UL 514B, CSA C22.2 .....