



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



GASK853N 1-In Neo Body Gas

Crouse-Hinds

Catalog Number	GASK853N
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 8 Gasket, Neoprene, 1", Solid
Weight per unit	0.0300 (lbs/each)
Product Category	Bodies & Covers

Features

connection	Water Jet Cut
dimensions	1.8100 IN X 0.0600 IN X 5.5900 IN
Material	Neoprene

Material, Color, and Finish

Color	Black
Finish	Black

Descriptions

Description	1-IN NEO BODY GAS
extra long description	CRS-H GASK853N 1 SOLID NEO FORM 8 G
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 8 bodies are offered in seven different shapes to provide the most flexible offering on the market. Form 8 Condulet outlet bodies provide more room for heavier conductors. Many shapes and sizes are available for rigid threaded conduit. Two cover screws on all body sizes provide tight
Long Description	Eaton Crouse-Hinds series Condulet Form 8 gasket, Neoprene, 1", Solid
Product Type	1 Solid Neo Form 8 Gask

Manufacturer Information

Brand	Eaton
GTIN	00782274438603
Manufacturers Part Number	GASK853N
UPC	782274438603

Taxonomies, Classifications, and Categories

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Type	Gasket



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Availability

Status	Inactive
--------	----------

Packaging

Carton	1
--------	---

Package	100
---------	-----

Weight Per each	0.03
-----------------	------

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
-------------	----------------------------------------------------------------------

standard	UL 514B, CSA C22.2
----------	--------------------