

GC2626CT, Mechanical Ground Clamp for Cable Tray

By Burndy Catalog # GC2626CT

Cable Tray Ground Clamp, Cast CU Alloy, #2 Sol., 2/0 Str. AL or CU, 1.70 in Width, Tin Plated.



Yes

Application

For Direct Burial Applications In Concrete Or Earth And For Used With Aluminum Or Galvanized Steel Cable Tray

General

EU RoHS Indicator Yes

Installation Torque 240 LBS/in

Recommended in-lb

Material Copper Alloy

Plated '

Plating Type Tin Plated

Sub Brand MECHANICAL CONNECTOR

Type GC-CT

UPC 781810220573 UPC 12 Digit 7818102205733

Dimensions

Dimension - B Length inch

Dimension - Cross Flats inch

Dimension - Height inch

Dimension - Width inch

Dimension - Width mm

1.12 in

0.56 in

1.95 in

1.70 in

43 mm

Conductor Related

Conductor - AL Str Size 2 AWG;1 AWG;1/0 AWG;2/0

AWG

Conductor - AL Str Size 2 AWG-2/0 AWG

Range

Conductor - Copper Solid Size 2 AWG;1 AWG;1/0 AWG;2/0

AWG

Conductor - Copper Solid Size 2 AWG-2/0 AWG

Range

Conductor - Copper Str Size 2 AWG;1 AWG;1/0 ;2/0 AWG

Conductor - Copper Str Size 2 AWG-2/0 AWG

Range

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance	EX

UL Listed **Logistics**

Minimum Pack Quantity 1

Product Assets

3D Models - GC2626CT_MODEL-PDF 3D Models - GC2626CT_MODEL-STEP 3D Models - GC2626CT_MODEL-IGES Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - sc082752-01

