



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3804 South Street
75964-7263, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



GTC162Q 4/0 T Mold to 5/8 GRC

Erico, Inc. Eritec-Caddy

Catalog Number	GTC162Q
Manufacturer	Erico, Inc. Eritec-Caddy
Description	Cable to Ground Rod, 5/8 In Rod Size, #4/0 Awg Conductor Size
Weight per unit	3.5 (lbs/each)
Product Category	Ground Rods & Grounding System

Descriptions

Description	4/0 T MOLD TO 5/8 GRC
-------------	-----------------------

Manufacturer Information

Brand	nVent ERICO
GTIN	00782856536642
sub brand	Pentair
UPC	782856536642

Taxonomies, Classifications, and Categories

Category Description	EXOTHERMIC GROUNDING PRODUCTS
Type	GT


Packaging

Carton	1
Weight Per each	3.5274

Uses, Certifications, and Standards

standard	None Mount
----------	------------

Cable to Ground Rod or Other Rounds – GTC162Q



ERICO CADWELD graphite molds are designed and engineered for thousands of connection styles and conductor combinations.

- Forms a permanent, low resistance connection
- Provides a molecular bond
- ERICO CADWELD Exothermic Connections are rated with the same current capacity as the conductor
- Portable installation equipment with no external source of power required
- Installers can be easily trained to make ERICO CADWELD Exothermic Connections
- Connections can be visually inspected



Part Number	GTC162Q
Mold Family	GT
Ground Rod Type	Copper-bonded
Ground Rod Diameter, Nominal	5/8"
Ground Rod Diameter, Actual	0.563"
Conductor Size	4/0 Concentric
Conductor Outer Diameter, Nominal	0.528"
Kit	No
Split Crucible	No
Wear Plates	No
Mold Only	No
Welding Material	115 or 115PLUSF20, Sold Separately
Handle Clamp	L160, Sold Separately
Price Key	C
Ease of Use	Preferred
Certifications	cULus

Part Number	GTC162Q
Standard Packaging Quantity	1 pc
UPC	78285653664
EAN-13	8711893157727

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless ERICO CADWELD EXOLON mold. Add an XL prefix to the standard mold part number when ordering (for example, a TAC2Q2Q becomes XLTAC2Q2Q). Similarly, ERICO CADWELD EXOLON welding material is also designated by the XL prefix (for example, 150 becomes XL150).

A gap between conductors may be required. See mold tag for more information.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.