

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

GUAB26 3/4" Guab Conduit Outlet Box *Crouse-Hinds*

| Crouse-Hinds | |
|----------------------------------|---|
| Catalog Number | GUAB26 |
| Manufacturer | Crouse-Hinds |
| Description | Conduit Outlet Box With Cover, Electrogalvanized and Aluminum Acrylic Paint (Body); Natural (Cover), LB Body Type, 3/4 In Trade Size, Threaded Connection, Round, 3 In (Cover) Opening Size, 2 Hubs, 3/4 In Hub Size, (1) Side; (1) Down Hub Location, LB Configuration, 3-1/2 In Width, 2 In Height, 2.35 LB/Ea |
| Weight per unit | 2.4 (lbs/each) |
| Product Category | Bodies & Covers |
| Features | |
| Cable Entry | (1) Side, (1) Down |
| dimensions | 3.5000 IN X 2.0000 IN X 4.3800 IN |
| Dimensions and Weight | |
| Size | 3/4 in |
| Descriptions | |
| Construction | Explosionproof, Dust-Ignitionproof, Raintight |
| Description | 3/4" GUAB CONDUIT OUTLET BOX |
| extra long description | CRS-H GUAB26 3/4 OUTLET BX 3 DIA CV |
| Features | Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | |
| UPC | 782274461403 |
| Taxonomies, Classifications, and | • |
| Category Description | |
| Туре | Conduit outlet box with cover |
| Packaging Carton | 1 |
| | |

2.35

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Mounting | PAD |
|----------|-------------------|
| standard | UL 886, CSA C22.2 |