

Contraction of

Туре

ELLIOTE ELECTRIC SUPPLY Ma Deliver Lower Cost Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

. .

~

Catalog Number	GUAC16SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Gua Conduit Outlet Box Wit Cover, 3" Cover Opening Diameter, Copper-Free Aluminum, C Shape, 1/2"
Weight per unit	1.2 (lbs/each)
Product Category	Alum
tures	
Cable Entry	Feed Through
dimensions	5.2500 IN X 2.0000 IN X 3.5000 IN
nensions and Weight	
Size	1/2 in
scriptions Construction	Explosionproof, Dust-Ignitionproof, Raintight
Description	1/2" GUAC COND OUTLET BOX
extra long description	CRS-H GUAC16 SA 1/2 AL OUTL BX 3 CV
Features	Crouse-Hinds series GUA and GUR explosionproof conduit outle boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th
Long Description	Eaton Crouse-Hinds series Condulet GUA conduit outlet box with cover, 3" cover opening diameter, Copper-free aluminum, C shape, 1/2"
Product Type	1/2 AL OutLRX 2 CV/D THPD Digid/Imc
Special Features	With Cover, Cover Opening Diameter 3 In
nufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274100319
Manufacturers Part Number	GUAC16 SA
UPC	782274100319

Conduit outlet box with cover



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Package	2
Weight Per each	1.15

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	PAD
standard	UL 886, CSA C22.2