ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
3168 SW Loop 436
75633-0000, TX Carthage
Phone: 903-694-9924
Fax: 903-694-9928



# GUAL16 1/2" Gual Conduit Outlet Box

*Crouse-Hinds*

| | |
|---|---|
| Catalog Number | GUAL16 |
| Manufacturer | Crouse-Hinds |
| Description | Conduit Outlet Box With Cover, Electrogalvanized and Aluminum Acrylic Paint (Body);Natural (Cover), L Body Type, 1/2 In Trade Size, Threaded Connection, Round, 3 In (Cover) Opening Size, 2 Hubs, 1/2 In Hub Size, (2) Side Hub Location, L Configuration, 3-1/2 In Width, 2 In Height, (4) Pad, 2.25 LB/Ea |
| Weight per unit | 2.3 (lbs/each) |
| Product Category | Bodies & Covers |

## Features

| | |
|---|---|
| Cable Entry | (2) Side |
| dimensions | 4.3800 IN X 2.0000 IN X 4.3800 IN |

## Dimensions and Weight

| | |
|---|---|
| Size | 1/2 in |

## Descriptions

| | |
|---|---|
| Construction | Explosionproof, Dust-Ignitionproof, Raintight |
| Description | 1/2" GUAL CONDUIT OUTLET BOX |
| extra long description | CRH GUAL16 1/2 CST IRON ROUND BASE |
| Features | Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th |

## Manufacturer Information

| | |
|---|---|
| Brand | Eaton |
| GTIN | 00782274464800 |
| UPC | 782274464800 |

## Taxonomies, Classifications, and Categories

| | |
|---|---|
| Category Description | HUB STYLE BOXES (GUAB, GUAT, ETC) |
| Type | Conduit outlet box with cover |

## Packaging

| | |
|---|---|
| Carton | 2 |
| Weight Per each | 2.25 |

3168 SW Loop 436
75633-0000, TX Carthage
Phone: 903-694-9924
Fax: 903-694-9928

## Uses, Certifications, and Standards

| | |
|---|---|
| standard | UL 886, CSA C22.2 |