



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2805 Poplar
75402-0000, TX Greenville
Phone: 903-454-3354
Fax: 903-454-8926



H100X034H1TB .34X1" 5000LBL WHT HS *Panduit Corporation*

Catalog Number	H100X034H1TB
Manufacturer	Panduit Corporation
Description	The H100X034H1T-B Military-Grade Polyolefin Heat-Shrink Label Is Single-Sided Printable. It Offers Crisp, Clear Legends With Superior Readability For Quick and Easy Label Production. The Heat-Shrink Sleeve Is Designed to Provide A Clear, Reliable, and Durable Way to Identify Wires and Cables. Shrink Ratio 3:1. 0.34" X 1" (8.6 MM X 25.4 MM). Color White. 5000 Labels Per Roll.
Weight per unit	5.4 (lbs/each)
Product Category	Markers & Marking Tapes

Features

labels per package	5000
Material	Polyolefin
Printer Type	THERMAL TRANSFER
Temperature Range	275

Material, Color, and Finish

Color	White
-------	-------

Dimensions and Weight

Length	NA
Size	1.00 x 0.34
Width	1

Descriptions

Description	.34X1" 5000LBL WHT HS
extra long description	PAN H100X034H1T-B H100X034H1T-B Hea
Long Description	The H100X034H1T-B Military-Grade Polyolefin Heat-Shrink Label is single-sided printable. It offers crisp, clear legends with superior readability for quick and easy label production. The heat-shrink sleeve is designed to provide a clear, reliable, and durable way to identify wires and cables. Shrink ratio 3:1. 0.34" x 1" (8.6 mm x 25.4 mm). Color White. 5000 labels per roll.
Product Type	H100X034H1T-B Heatshrink, Po, White, Mil Grade, 5000 LBLS, T

Manufacturer Information

Brand	Panduit Corporation
GTIN	00074983522255
Manufacturers Part Number	H100X034H1T-B
UPC	074983522255



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2805 Poplar
75402-0000, TX Greenville
Phone: 903-454-3354
Fax: 903-454-8926

Taxonomies, Classifications, and Categories

Type Heat Shrink Label

Packaging

Carton 1

Weight Per roll 5.35

Uses, Certifications, and Standards

standard Meets UL Standard 224 for flammability and AMS-DTL-23053/5C (Class 1 and Class 3). Meets SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and D202F, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin or hybrid therm