




# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

21330 Inverness Forest Blvd  
77073-0000, TX Houston  
Phone: 832-626-1994  
Fax: 832-626-1995



## H150X034H1TB TT, HS, Tubing, 1.5"WX.34"H, Panduit Corporation

Catalog Number	H150X034H1TB
Manufacturer	Panduit Corporation
Description	The H150X034H1T-B Military-Grade Polyolefin Heat-Shrink Label Is A Single-Sided Printable. It Offers Crisp, Clear Legends With Superior Readability For Quick and Easy Label Production. The Heat-Shrink Sleeve Is Designed to Provide A Clear, Reliable, and Durable Way to Identify Wires and Cables. Designed For Use With Panduit TDP Printers. Shrink Ratio 3:1. 1.5" X 0.34" (38.1 MM X 8.6 MM). Color White. 2500 Labels Per Roll.
Weight per unit	5.3 (lbs/each)
Product Category	Markers & Marking Tapes

### Features

labels per package	2500
Material	Polyolefin
Printer Type	THERMAL TRANSFER
Temperature Range	275

### Material, Color, and Finish

Color	White
-------	-------

### Dimensions and Weight

Length	NA
Size	1.50 x 0.34
Width	1.5

### Descriptions

Description	TT,HS,TUBING,1.5"WX.34"H,
extra long description	PAN H150X034H1T-B H150X034H1T-B Hea
Long Description	The H150X034H1T-B Military-Grade Polyolefin Heat-Shrink Label is a single-sided printable. It offers crisp, clear legends with superior readability for quick and easy label production. The heat-shrink sleeve is designed to provide a clear, reliable, and durable way to identify wires and cables. Designed for use with Panduit TDP printers. Shrink ratio 3:1. 1.5" x 0.34" (38.1 mm x 8.6 mm). Color White. 2500 labels per roll.
Product Type	H150X034H1T-B Heatshrink, Po, White, Mil Grade, 2500 LBLS, T



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

21330 Inverness Forest Blvd  
77073-0000, TX Houston  
Phone: 832-626-1994  
Fax: 832-626-1995

## Manufacturer Information

Brand	PANDUIT
GTIN	00074983522835
Manufacturers Part Number	H150X034H1T-B
UPC	074983522835

## Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Heat Shrink Label

## Packaging

Carton	1
Weight Per roll	5.3499

## Uses, Certifications, and Standards

standard	Meets UL Standard 224 for flammability and AMS-DTL-23053/5C (Class 1 and Class 3). Meets SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and D202F, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin or hybrid therm
----------	--