



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



H200X240H1T 2.4X2" WHT Mltry Grade HS LBL *Panduit Corporation*

Catalog Number	H200X240H1T
Manufacturer	Panduit Corporation
Description	The H200X240H1T Military-Grade Polyolefin Heat-Shrink Label Is A Single-Sided Printable. It Offers Crisp, Clear Legends With Superior Readability For Quick and Easy Label Production. The Heat-Shrink Sleeve Is Designed to Provide A Clear, Reliable, and Durable Way to Identify Wires and Cables. Designed For Use With Panduit TDP Printers. Shrink Ratio 3:1. 2" X 2.4" (50.8 MM X 61 MM). Color White.100 Labels Per Roll.
Weight per unit	1.2 (lbs/each)
Product Category	Insulating Materials

Features

labels per package	100
Material	Polyolefin
Printer Type	THERMAL TRANSFER
Temperature Range	275

Material, Color, and Finish

Color	White
-------	-------

Dimensions and Weight

Length	NA
Size	2.00 x 2.40
Width	2

Descriptions

Description	2.4X2" WHT MLTRY GRADE HS LBL
extra long description	PAN H200X240H1T H200X240H1T Heatshr
Long Description	The H200X240H1T Military-Grade Polyolefin Heat-Shrink Label is a single-sided printable. It offers crisp, clear legends with superior readability for quick and easy label production. The heat-shrink sleeve is designed to provide a clear, reliable, and durable way to identify wires and cables. Designed for use with Panduit TDP printers. Shrink ratio 3:1. 2" x 2.4" (50.8 mm x 61 mm). Color White.100 labels per roll.
Product Type	H200X240H1T Heatshrink, Po, White, Mil Grade, 100 LBLs, TT,



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	PANDUIT
GTIN	00074983730605
Manufacturers Part Number	H200X240H1T
UPC	074983730605

Taxonomies, Classifications, and Categories

Type	Heat Shrink Label
------	-------------------

Packaging

Carton	1
Weight Per roll	1.2

Uses, Certifications, and Standards

standard	Meets UL Standard 224 for flammability and AMS-DTL-23053/5C (Class 1 and Class 3). Meets SAE-AS81531, MIL-STD-883F Method 2015.13, Solutions A, B, and D, and D202F, and MIL-STD-202G Method 215K, Solutions A, C, and D when printed with resin or hybrid therm
----------	--