



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2202 East Rusk Street
75766-0000, TX Jacksonville
Phone: 903-586-2904
Fax: 903-586-5271



HBL2320ST LKG RCPT, 20A 250V, L6-20R, BK, Spring T *Hubbell Wiring Devices*

| | |
|------------------|---|
| Catalog Number | HBL2320ST |
| Manufacturer | Hubbell Wiring Devices |
| Description | 20A, 250V Edgeconnect™ Twist-Lock® Receptacle With Spring Termination |
| Weight per unit | 0.1390 (lbs/each) |
| Product Category | 20230614140645 |

Features

| | |
|---------------------|---|
| connection | Spring Termination |
| Dielectric Strength | Withstands 2,000V minimum |
| insulation | False |
| Material | Nylon |
| Number of Wires | 3 |
| pallet quantity | 3060 |
| Phase | 1 |
| Poles | 2 |
| Voltage Rating | 250 V |
| Wattage | 5,000 |
| Wire Size | 14 - 10 solid, 14 - 8 stranded (including compact stranded) |

Dimensions and Weight

| | |
|------|--|
| Size | 3.28 in x 1.70 in x 1.47 in;Standard Sized Product |
|------|--|

Descriptions

| | |
|------------------------|---|
| Description | LKG RCPT, 20A 250V, L6-20R, BK, SPRING T |
| extra long description | HWDK HBL2320ST LKG RCPT, 20A 250V, |
| Long Description | 20A, 250V EdgeConnect™ Twist-Lock® Receptacle with Spring Termination |
| Product Type | LKG RCPT, 20A 250V, L6-20R, BK, Spring T |
| Special Features | Twist-Lock Receptacle with Spring Termination |

Manufacturer Information

| | |
|---------------------------|-----------------------|
| Brand | WIRING DEVICE-KELLEMS |
| GTIN | 00783585569550 |
| Manufacturers Part Number | HBL2320ST |
| UPC | 783585569550 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--------------------------|
| Category Description | Fuses & Fuse Accessories |
|----------------------|--------------------------|



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2202 East Rusk Street
75766-0000, TX Jacksonville
Phone: 903-586-2904
Fax: 903-586-5271

Packaging

| | |
|-----------------|-------|
| Carton | 1 |
| Package | 30 |
| Weight Per each | 0.139 |

Uses, Certifications, and Standards

| | |
|--------------------------|---|
| Application | Heavy Duty Industrial |
| environmental conditions | Indoor Dry unless protected by additional means |
| Mounting | Screw Mount |
| nema rating | L6-20R |
| standard | CSA Certified to Specification C22.2 No. 42;UL Listed To UL 498;WR Rating |