# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2301 East Saint Elmo Rd. Suite 105
78744-0000, TX Austin
Phone: 512-443-5600
Fax: 512-443-5601

## HCLR15 15A 600V Class CC Fast Acting Fuse
*Edison Fuses*

| | |
|---|---|
| Catalog Number | HCLR15 |
| Manufacturer | Edison Fuses |
| Description | Class CC Fuse, 15 A, 600 V Ac, Melamine (Body);Brass (End Cap) Material, 0.41 In Diameter, 1.50 In Overall Length, 0.02 LB |
| Weight per unit | 0.0200 (lbs/each) |
| Product Category | Renewable & Non-Renewable |

### Features

| | |
|---|---|
| amperage rating | 15 |
| class | Class CC |
| dimensions | 1.0000 IN X 0.4060 IN X 0.4060 IN |
| media | Yes |

### Dimensions and Weight

| | |
|---|---|
| Height | 0.406 |
| Length | 1 |
| Width | 0.406 |

### Descriptions

| | |
|---|---|
| Description | 15A 600V CLASS CC FAST ACTING FUSE |
| extra long description | EFSE HCLR15 UL CLASS CC FAST ACTING |
| Features | Edison offers a complete line of Class CC fuses to meet your circuit and equipment protection needs. These branch circuit rated compact fuses rated 600v, and delivering 200,000a IR Vac Sym provide excellent protection in the smallest package of any UL class of fuses. Choose from our EDCC time-delay fuses for your small horsepower motor circuits, our HCLR fast-acting for your non-inductive lighting and resistance heating loads or our HCTR time-delay fuses for your small control transformer protection. |
| Special Features | Rejection Style |

### Manufacturer Information

| | |
|---|---|
| Brand | Eaton |
| GTIN | 00782634420705 |
| Manufacturers Part Number | T626-HCLR15 |
| UPC | 782634420705 |

### Taxonomies, Classifications, and Categories

| | |
|---|---|
| Category Description | MIDGET FUSES |
| Type | FUSE |

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2301 East Saint Elmo Rd. Suite 105
78744-0000, TX Austin
Phone: 512-443-5600
Fax: 512-443-5601

## Packaging

| | |
|---|---|
| Carton | 1 |
| Package | 10 |
| Weight Per each | 0.02 |

## Uses, Certifications, and Standards

| | |
|---|---|
| Application | Datacenters - Facilities: Critical Power |
| standard | UL Listed,CSA Certified,CE Marked,RoHS Compliant |