

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HFD3030 Type HFD 3 Pole 30A Trip 600V Class 65KA At 480V W Eaton Corp

Catalog Number	HFD3030
Manufacturer	Eaton Corp
Description	Eaton Series C Complete Molded Case Circuit Breaker, F-Frame, HFD, Complete Breaker, Fixed Thermal, Fixed Magnetic Trip Type Three-Pole, 30 A, 600 Vac, 250 VDC, Load Side, 50/60 HZ
Weight per unit	4.3 (lbs/each)
Product Category	3 Pole
tures	
Current Rating	30 A
dimensions	3.3800 IN X 4.1300 IN X 6.0000 IN
media	Yes
Poles	3
Trip Type	Fixed thermal, fixed magnetic
Voltage Rating	600 VAC, 250 VDC
scriptions	
Description	TYPE HFD 3 POLE 30A TRIP 600V CLASS 65KA AT 480V W
extra long description	ETN HFD3030 Eaton Series C complete
Features	Experience the superior quality of the Eaton Series C Molded
	Case Circuit Breaker. The Series C circuit breaker is ideal
	for panelboards, switchboards, motor control centers, and
	busway applications. Choose from a premier selection of trip
	units including thermal magnetic, electronic, and magnetic only
	switches. Available for systems up to 600 VAC or 250 VDC with
	current ratings up to 800A.
Long Description	Eaton Series C complete molded case circuit breaker, F-frame,
	HFD, Complete breaker, Fixed thermal, Fixed magnetic trip type
Product Type	Three-pole, 30 A, 600 Vac, 250 Vdc, Load side, 50/60 Hz Eaton Series C Complete MCCB
5.	Laton series c complete McCb
nufacturer Information	F
Brand	Eaton Corp
GTIN	00786679175804
Manufacturers Part Number	HFD3030
UPC	786679175804

T

Category Description	MOLDED CASE BREAKERS
Туре	Molded case circuit breaker



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

P	a	C	K	a	g	I	n	g

Carton	1	
Weight Per each	4.25	

Uses, Certifications, and Standards

Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies and FOFMs - Other
Frequency Rating	50/60 Hz
standard	UI Listed