



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2255 Northwest Parkway SE  
30067-0000, GA Marietta  
Phone: 678-398-4904  
Fax: 678-398-4905

## **HSTT150C 1-1/2-3/4" 100' BLK Thinwall HS Tube** *Panduit Corporation*

Catalog Number	HSTT150C
Manufacturer	Panduit Corporation
Description	The HSTT150-C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 1.50" Diameter X 100' Long (38.1 MM X 30.5 M). Color Black. 1 Roll.
Weight per unit	6.1 (lbs/each)
Product Category	Insulating Materials

### **Features**

flammability	Flame Retardant
media	Yes
outside diameter	1.5
Shrink Ratio	2:1

### **Material, Color, and Finish**

Color	Black
-------	-------

### **Dimensions and Weight**

Thickness	0.04
-----------	------

### **Descriptions**

Description	1-1/2-3/4" 100' BLK THINWALL HS TUBE
extra long description	PAN HSTT150-C Dry-Shrink™ HSTT150-C
Long Description	The HSTT150-C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 1.50" Diameter x 100' Long (38.1 mm x 30.5 m). Color Black. 1 roll.
Product Type	Dry-Shrink™ HSTT150-C Heatshrink, Black, Po, 100' L, 1.5" to

### **Manufacturer Information**

Brand	Panduit®
GTIN	00074983914937
Manufacturers Part Number	HSTT150-C
UPC	074983914937



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2255 Northwest Parkway SE  
30067-0000, GA Marietta  
Phone: 678-398-4904  
Fax: 678-398-4905

## Taxonomies, Classifications, and Categories

Type ..... Heat-Shrink .....

## Packaging

Carton ..... 1 .....

Weight Per roll ..... 6.11 .....

## Uses, Certifications, and Standards

Application ..... For Dry Locations;Insulating and protecting wires and cables .....

standard ..... Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770 .....