



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

HSTT38C .375"X100' BLK Thin Wall HS *Panduit Corporation*

| | |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number | HSTT38C |
| Manufacturer | Panduit Corporation |
| Description | The HSTT38-C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.375" Diameter X 100' Long (9.5 MM X 30.5 M). Color Black. 1 Roll. |
| Weight per unit | 1.1 (lbs/each) |
| Product Category | Insulating Materials |

Features

| | |
|------------------|-----------------|
| flammability | Flame Retardant |
| media | Yes |
| outside diameter | 0.37 |
| Shrink Ratio | 2:1 |

Material, Color, and Finish

| | |
|-------|-------|
| Color | Black |
|-------|-------|

Dimensions and Weight

| | |
|-----------|-------|
| Thickness | 0.025 |
|-----------|-------|

Descriptions

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | .375"X100' BLK THIN WALL HS |
| extra long description | PAN HSTT38-C Dry-Shrink™ HSTT38-C H |
| Long Description | The HSTT38-C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.375" Diameter x 100' Long (9.5 mm x 30.5 m). Color Black. 1 roll. |
| Product Type | Dry-Shrink™ HSTT38-C Heatshrink, Black, Po, 100' L, 0.375" T |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Panduit® |
| GTIN | 00074983747047 |
| Manufacturers Part Number | HSTT38-C |
| UPC | 074983747047 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Type Heat-Shrink

Packaging

Carton 1

Weight Per roll 1.14

Uses, Certifications, and Standards

Application For Dry Locations;Insulating and protecting wires and cables

standard Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770