



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

HSTT50C 1/2"X100' BLK Thin Wall HS *Panduit Corporation*

Catalog Number	HSTT50C
Manufacturer	Panduit Corporation
Description	The HSTT50-C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.50" Diameter X 100' Long (12.7 MM X 30.5 M). Color Black. 1 Roll.
Weight per unit	1.8 (lbs/each)
Product Category	Insulating Materials

Features

flammability	Flame Retardant
media	Yes
outside diameter	0.5
Shrink Ratio	2:1

Material, Color, and Finish

Color	Black
-------	-------

Dimensions and Weight

Thickness	0.025
-----------	-------

Descriptions

Description	1/2"X100' BLK THIN WALL HS
extra long description	PAN HSTT50-C Dry-Shrink™ HSTT50-C H
Long Description	The HSTT50-C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.50" Diameter x 100' Long (12.7 mm x 30.5 m). Color Black. 1 roll.
Product Type	Dry-Shrink™ HSTT50-C Heatshrink, Black, Po, 100' L, 0.5" to

Manufacturer Information

Brand	Panduit®
GTIN	00074983747054
Manufacturers Part Number	HSTT50-C
UPC	074983747054



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Type Heat-Shrink

Packaging

Carton 1

Weight Per roll 1.8

Uses, Certifications, and Standards

Application For Dry Locations;Insulating and protecting wires and cables

standard Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770