



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

HSTT50CC 1/2"X100' CLR Thin Wall HS *Panduit Corporation*

Catalog Number	HSTT50CC
Manufacturer	Panduit Corporation
Description	The HSTT50-CC Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Cross-Linked Polyolefin. 0.50" Diameter X 100' Long (12.7 MM X 30.5 M). Color Clear. 1 Roll.
Weight per unit	0.1800 (lbs/each)
Product Category	Insulating Materials

Features

flammability	N/A
media	Yes
outside diameter	0.5
Shrink Ratio	2:1

Material, Color, and Finish

Color	Colorless
-------	-----------

Dimensions and Weight

Thickness	0.025
-----------	-------

Descriptions

Description	1/2"X100' CLR THIN WALL HS
extra long description	PAN HSTT50-CC Dry-Shrink™ HSTT50-CC
Long Description	The HSTT50-CC Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Cross-linked polyolefin. 0.50" Diameter x 100' Long (12.7 mm x 30.5 m). Color Clear. 1 roll.
Product Type	Dry-Shrink™ HSTT50-CC Heatshrink, Clear, Po, 100' L, 0.5" to

Manufacturer Information

Brand	PANDUIT
GTIN	00074983747207
Manufacturers Part Number	HSTT50-CC
UPC	074983747207



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Heat-Shrink

Packaging

Carton	1
Weight Per roll	0.18

Uses, Certifications, and Standards

Application	For Dry Locations;Insulating and protecting wires and cables
standard	Mil Spec: AMS-DTL-23053/5 Class 2