Straight Blade Devices

20A, 125V, 2 Pole, 3 Wire Grounding

HBL® Extra Heavy Duty MAX Specification Grade **Duplex Receptacle**

Features

- · Triangle marking on face indicates isolated ground
- Slender compact design
- Finder Groove Face

Ordering Information

Description Isolated ground, back and side wired.

Device Color Red

UPC Number 783585876894 **Catalog Number** IG5362R

Listings

UL Listed to UL498 File No. E2186 Certified to CSA, C22.2, No. 42 File 285 Fed. Spec. WC596 NEMA® WD-6 Compliant

Specifications

Face Nylon **PBT** Base

Contacts 0.031" (0.8) Brass Clamp Nickel plated steel

Terminal Screws Brass

Mounting Strap .050 in. (1.3) Brass Automatic Self-grounding Clip Stainless steel Mounting Screws Zinc plated steel

Performance

Electrical

Current Interrupting

Certified for current interrupting at full rated

Dielectric Voltage Withstands 2,000V minimum

Mechanical

Product Identification **Terminal Accommodation** Terminal Identification

Ratings are a permanent part of the device #12-#10 AWG stranded or solid copper wire only Terminals identified in accordance with UL 498

and CSA

Environmental

Flammability Top: UL 94V-2. Base: UL 94V-0


Operating Temperatures Maximum continuous 75°C; minimum -40°C (w/o

impact)

HUBBELL







Complementary Products

Wallplate or Weatherproof Cover **Duplex Opening**

Online Resources

Customer Sales Drawings eCatalog

Installation Instructions

