


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





IPCS4020 4/0-2, 2/0-6 Insulation Piercing Connector *Nsi Industries*

*	ID 00 1000	
Catalog Number	IPCS4020	
Manufacturer	Nsi Industries	
Description	Insulation Piercing Connector 4/0 - 2 Awg Insulation Piercing Connectors Are Made For Use With Copper-Copper, Copper to Aluminum and Aluminum to Aluminum Applications. They Are Safe to Use and Are Completely Insulated, No Need to Strip Wire. They Can Be Installed On Energized Conductors With No Contact At Any Point. No Spacer Required Between Connections.	
	Exclusive "Turbo Spacer" Keeps Tap Side Open While Main Conductor Is Being Tightened. Watertight and Corrosion-Free.	
Weight per unit	0.4100 (lbs/each)	
Product Category	Large Terminals & Connectors	
Features		
amperage rating	300 (CU Amps) - 235 (AL Amps)	
Conductor Size	4/0-2 AWG (Main)	
Material	Fibor Deinfersed Thermal Diestic	
Tap Size	2/0-6 AWG	
Voltage Rating	600 V	
Material, Color, and Finish		
Color		
Finish	Thermal Plastic	
Dimensions and Weight		
Size	L=2.60 - W=2.20 - H=3.30	
Descriptions		
Description	4/0-2, 2/0-6 INSULATION PIERCING CONNECTOR	
extra long description	NSI IPCS4020 Insulation Piercing Co	
Long Description	Insulation Piercing Connector 4/0 - 2 AWG Insulation piercing connectors are made for use with copper-copper, copper to aluminum and aluminum to aluminum applications. They are safe to use and are completely insulated, no need to strip wire. They can be installed on energized conductors with no contact at any point. No spacer required between connections. Exclusive "turbo	
	spacer" keeps tap side open while main conductor is being tightened. Watertight and corrosion-free.	
Product Type	Insulation Piercing Connector 4/0-2/0 Aw	
Special Features	No need to strip wire - No tape or cover needed - Exclusive turbo spacer keeps tap side open while main conductor is being tightened	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

nufacturer Information		
Brand	NSi	
GTIN	00662381082657	
Manufacturers Part Number	IPCS4020	
UPC	662381082657	

Category Description	SPLII BOLIS	
Туре	Insulation Piercing Connectors	
Availability		

Status	Inactive
Packaging	
Carton	1

Carton	1	
Package	4	
Weight Per each	0.41	
•		

Uses, Certifications, and Standards	
Application	NSI
environmental conditions	90 C
Mounting	Clamp
standard	UL486B Listed
Temperature Rating	90 C