


# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service





#### IPLD5004 500MCM-#4 4 Pole Polaris Connector Block Nsi Industries

Catalog Number	IPLD5004
Manufacturer	Nsi Industries

Multi-Tap Connector, #4 Awg Conductor Size, 500 MCM Description

Conductor Size, Insulated, Plastisol Insulation Material,

Copper/Aluminum Conductor Material, Black Insulation Color, 4 Conductors, -45 °C Operating Temperature, +90 °C Operating Temperature, 5.24 In Overall Length, 600 V, 1.0499 LB/Ea

1.0 (lbs/each) Weight per unit

Product Category Large Terminals & Connectors

#### **Features**

1 Poles

600 V Voltage Rating 1 YEAR Warranty

Wire Size 500 MCM-4 AWG

Wire Type Class B & C

### Material, Color, and Finish

Color Black

Plastisol Insulated Finish

Housing Material Aluminum

# **Dimensions and Weight**

Size L=5.240 - W=2.830 - H=2.910

# **Descriptions**

Description 500MCM-#4 4 POLE POLARIS CONNECTOR BLOCK

extra long description NSI IPLD500-4 POLARIS Ins Multi-Tap

**Features** The Polaris IPLD500-4 4-Port Dual-Sided Connector provides the

simplest solution for forming a secure connection between up to four conductors in applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 500 MCM - 4 AWG wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated connector options using just a hex key and torque wrench. The aluminum alloy body is wrapped in

high-dielectric stre

#### Manufacturer Information

GTIN 00662381925022 **UPC** 662381925022



environmental conditions

standard

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

90 C

UL 486A/B

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categ	ories
Category Description	
Туре	Double Sided Entry
Packaging	
Carton	3
Weight Per each	1.0499
Uses, Certifications, and Standards	
Application	Wire Termination